

PIPING REQUIREMENTS

- 1. Applicant must contact the Engineering Division at 724-3761 (75 Calhoun Street) to obtain a permit for installation of the pipe.**
- 2. Either the homeowner, or a licensed contractor, shall install the pipe in accordance with the South Carolina Department of Transportation Specifications, Section 714 for Pipe Culverts.**
- 3. For ditches within the right-of way, applicant is required to purchase Class III concrete pipe, the diameter of which is determined by the adjacent downstream pipe unless noted otherwise on the permit. For piping easements, applicant may use Class III concrete or HDPE pipe. If there is no adjacent downstream pipe, a minimum 15-inch diameter pipe shall be required, however, a review by the Engineering Division may specify larger pipe upon review of the permit application.**
- 4. Prior to backfilling, the applicant shall contact the city's inspector and have the pipe inspected for proper sealing, alignment and grade. If assistance is needed in the installation process, the applicant can contact the Engineering Division and request such assistance.**
- 5. Once the pipe has been approved, the contractor may proceed with the construction of the driveway, if applicable, in accordance with the requirements above and any special conditions attached to the permit.**
- 6. Failure to adhere to these requirements may result in disapproval until corrections are made. If applicant fails to make the corrections, the city may elect to perform the corrections and the applicant will be responsible for any costs incurred by the city in the course of the work.**
- 7. Any additional drainage facilities (junction boxes, catch basins, etc) shall be constructed in accordance with the city's standard specifications.**